

# Hurley M

Sea-View™

Underwater Lighting at a NEW Level



Hurley Marine  
Underwater Lighting  
Sea-View Series

Sea-View™

**Underwater Lights**

Patent # 7,448,780



**Trim Tab or  
Surface Mounted**

- Four 10 watt LED Array
- Equal to 50w Xenon
- 12/24vDC
- 40,000+ Hour Life
- Chemically Resistant Polymer
- Convex Borosilicate Glass
- 1/4" Hole for cable
- 2 Year Full-Factory Warranty

**Hurley Sea-View Lights™** raise the bar on range and brightness that rivals any other underwater light on the market.


The Sea-View is for underwater use but has a built-in thermal monitoring system so they can be used while under way. To aid in its cooling while lit, we've designed it with a water cooling system that allows it to maintain the lights cool and efficient for an ultra long life span.

Exceptionally easy to install and versatile enough to be mounted onto any transom, hull or add a trim tab bracket which is easily attached to all leveling systems. Systems are available for dock lights.

Maintenance is easy, just wipe away sea growth from its lens and backing plate.

## Quick Specs

40K+ HOURS	12v 10-30 VDC	4200	6500	BOROSILICATE	BEAM SPREAD	DISTANCE
LIFE SPAN	24v 10-30 VDC	FIXTURE LUMENS	FIXTURE KELVIN	OPTICAL LENS	75°	60'+



Description	Color	Part #
Sea-View Ultra White LEDs		SVU-1012W
Sea-View Ultra Blue LEDs		SVU-1012B
Sea-View Ultra Green LEDs		SVU-1012G
Sea-View Ultra Red LEDs		SVU-1012R

Mounting Recommendations		Sea-View
Boat size		Any
Transom spacing		1-1.5m (3-5')
Hull spacing		1-1.8m (3-6')
Trim Tabs		Stackable
Installation depth		10+cm (4" +)
Technical		
Light output equivalent to		50W Xenon
Fixture Lumens* (total output from a single fixture)		4200
Typical LED life expectancy		40,000+ Hours
Current / Amp draw (DC)		12vDC 3.A, 24vDC 1.5A
Light penetration (dependant upon water clarity)		up to 19m+ (60')
Driver type		Internal
Physical		
Length of fixture		210mm (8 <sup>1/2</sup> "
Width of fixture		518mm (2 <sup>5/8</sup> "
Profile (height) of fixture		32mm (1 <sup>1/4</sup> "
Total weight		972grms (1.76 lb)
Cable length (standard)		3m (10')
Hole cut-out for cable entry		6.35mm (1/4")
Material		Polyvinyl Chloride
Lens		Borosilicate Glass
Accessories		Part #
Trim Tab Brackets		SVU-1012BR
Remote Control Light Kit		SVU-1012RT
Switch Control Light Kit		SVU-1012SW

## Thermal Monitoring System



Overheat sensors are built in to our systems to prevent overheating, thus improving LED performance and lumen maintenance. In the event the lights become overheated, the system will reduce the LED power level in order to protect the LEDs. Sea-View's lights are tested to work continuously in an ambient temperature of 74° Centigrade / 165° Fahrenheit.

## Optic's



Sea-View lights incorporate revolutionary Borosilicate glass convex lens producing a 75 degree beam spread. This innovative design creates greater light dispersion and magnification for a dynamic underwater lighting effect.

The Sea-View Light is stackable using our trim tab brackets. You are able to add another light on-top of another using an additional trim tab bracket. Now you can have two different colors depending upon your mood.

