

LIMITED WARRANTY AND LIMITATION OF LIABILITY

All electrical components manufactured under Hurley Marine, Inc., are warranted to be free from defects in material and workmanship under normal and proper use for a period of 90 days from date of shipment from Hurley Marine, Inc. No claim for breach of warranty will be allowed unless the material or workmanship is found defective within the warranty period, properly documented by buyer and Hurley Marine, Inc. is notified in writing within 10 days from failure. This warranty shall not apply to products that have been disassembled, altered, or utilized in a manner not approved by Hurley Marine, Inc. or subjected to normal wear and tear, abuse, misuse, improper maintenance, negligence or accident.

CUSTOMER AGREES THAT USE OF THE PRODUCT/SERVICE IS ENTIRELY AT CUSTOMER'S OWN RISK. THE FOREGOING WARRANTIES ARE EXCLUSIVE AND ARE ACCEPTED BY BUYER IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. Buyer's sole remedy in the event of a breach of the forgoing warranties is the repair or replacement of the affected product by Hurley Marine, Inc., upon the return of the product transportation charges prepaid to Hurley Marine, Inc., and after a charge to buyer for the use of the product prior to its return. BUYER AGREES THAT IN NO EVENT WILL HURLEY MARINE, INC.'S LIABILITY FOR ALL LOSSES FROM ANY CAUSE, WHETHER BASED ON CONTRACT, NEGLIGENCE, STRICT LIABILITY, OTHER TORT OR OTHERWISE, EXCEED BUYER'S NET PURCHASE PRICE, NOR WILL HURLEY MARINE, INC. BE LIABLE FOR ANY SPECIAL, INCIDENTAL CONSEQUENTIAL OR EXEMPLARY DAMAGES.

Under no circumstances is Hurley Marine, Inc. responsible for reimbursement of expenses related to vessel haul-outs, technician or yard personnel, travel expenses, yacht storage, labor performed during removal and/or replacement of fixture(s), or shipping costs for replacement parts and/or repairs. These are assumed liabilities of the customer and part of the terms of sale between Hurley Marine, Inc. and its customer.

The foregoing warranties will continue in effect for so long as the product is serviced and maintained in accordance with Hurley Marine, Inc. instructions and with genuine Hurley Marine, Inc. manufactured replacement parts. These warranties may not be altered or amended except by a written instrument signed by buyer and a duly authorized officer of Hurley Marine, Inc. For warranty or service assistance contact your Hurley Marine, Inc. dealer.

TERMS OF SALE / SHIPPING

RETURN POLICY: If you are dissatisfied with your purchase, contact us within 30 days from the date of product purchase. Products returned within 30 days of their receipt, unopened in their original packaging and otherwise in new condition will automatically be exchanged or refunded. A minimum fee of 25% of the price of the product will be charged for inspection, repacking and restocking for items not returned in their original condition. Other fees may apply depending upon the condition of the item. Products are not returnable after 30 days.

EXCHANGE / REFUND PROCEDURE:

- All returns must have a copy of a paid invoice, contact information and a brief description of the reason accompanied with the return.
- Properly repack the product in the original packaging and place inside a box suitable for shipping with all the original enclosures, parts, and accessories.
- Return it with **original receipt** and postage pre-paid (we do not accept C.O.D.), add appropriate insurance.
- Shipping and packing fees are non-refundable.

Non-Returnable items: Inflatable boats, installed/mounted items, damaged goods, clearance/discount items, used and/or display items, electrical goods, light bulbs and special ordered items are not returnable, unless defective, and then for repair/replacement only. If the product is defective you must call Hurley Marine, Inc. within 10 days of receipt of the product.

DAMAGES GOODS: We thoroughly inspect all items prior to shipment. We suggest that you also thoroughly inspect the item(s) before accepting delivery. If damage is apparent, refuse delivery or if your parcel is left without a signature and damage is found contact the carrier immediately. Do not discard the box or any packaging materials. Most claims must be filed with the carrier within 10 days of receipt of delivery. Although we take special care to ensure the safe arrival of your merchandise, our responsibility for damage ends when the carrier accepts shipment.



LED Sea-Vue® Dock Light Instructions

IMPORTANT SAFETY INSTRUCTIONS

SAVE THESE INSTRUCTIONS: This manual contains important safety and operating instructions for Sea-Vue Underwater LED Dock lights. **CAREFULLY READ THESE INSTRUCTIONS BEFORE INSTALLING OR USING PRODUCT.**

GENERAL PRECAUTIONS



Do not operate the Sea-Vue Lights with damaged cables . . . Replace damaged product immediately.

VOLTAGE COMPATIBILITY: NEVER plug the Sea-Vue Dock Lights into a power receptacle other than what it is rated for.


MOUNTING LOCATIONS: The Sea-Vue Lights LED lights must be mounted at least 6" below the low tide waterline. The power supply should be mounted in a location with plenty of ventilation that is not likely to experience water submersion.

EXCESSIVE MOISTURE: Do not expose electrical connections to direct water contact or submersion.

LOCATION OF POWER CABLE: Make sure all electric power cable is located so that they cannot be stepped on, tripped over, chafed or otherwise be subjected to damage or stress.

LED Sea-View® Dock Light

- Control Box must be mounted on the external part of the dock.
- Photocell Eye must be kept clean and clear at all times.




- Lights can be redirected by loosening the screws on the back of the housing(s) to desired position.

RECEPTACLE AND CONNECTOR



30 A 125V
2-POLE, 3-WIRE



50 A 125/250V
3-POLE, 4-WIRE



Mounting Instructions:

- Select a mounting location best suited to your particular needs. Mount as so the light housing(s) are at least 6" below the low tide waterline.
 - Depending upon your application use two desired length screws or bolts thru the two studs to mount your mounting plate. Additional mounting plates can be purchased in order to move your light from berthing well to well.
 - Any changes to the wiring must be carried out by a suitably qualified electrician using ABYC guidelines. AC power supplies are IP67 (with temporary submersion less than 1m).
 - Sea-View Lights are equipped with an over temperature protection circuit that will dim the lights if they inadvertently over heat. Ensure the lens and backing plate are kept clean at all times. Failing to do so will result in excessive heat build up and poor light performance. Do not use abrasive or sharp objects to clean the housings and glass lens.
- Hint:** Spraying lights with Silicone or putting a thin layer of Petroleum Jelly on annually will help keep algae, mussels, barnacles, etc. off.
- Dismantling this product voids warranty.
 - Do not use as a step.

